4MSI Common Approach on Organic Materials in Contact with Drinking Water

Part B - Positive Lists

Adopted by the 4MSI Joint Management Committee

7th Revision-15 December 2023

France, Germany, the Netherlands, United Kingdom and Denmark work together in the framework of the 4MSI Common Approach as laid down in the Declaration of Intent (January 2011). This common approach aims for convergence of the respective national approval schemes for materials and products in contact with drinking water.

The 4MSI has adopted this document as a common basis for implementing the concept of a Positive List for the assessment of organic materials in their national regulations. The document is subject to revisions agreed by the 4MSI.

Further information may be obtained from any of the competent authorities of the 4MSI.

Bundesministerium für Gesundheit (Germany)
Ministère de la Santé et de la Prévention (France)
Ministerie van Infrastructuur en Waterstaat (The Netherlands)
Department for Environment, Food and Rural Affairs (United Kingdom)
Miljøministeriet (Denmark)

Introduction

An essential element of the regulatory arrangements for control of the hygienic performance of organic products in contact with Drinking Water (PDW's) is the examination and approval of the substances used for the production of these products. The goal of the 4MS Initiative is to have a Positive List of substances that are permitted for the production of organic materials, which is accepted by all MS's. This is in addition to the substances authorized for use in food contact materials (FCM) according to Regulation (EU) No. 10/2011, as these are included as permissible for use in PDW's.

Candidate substances for the Positive List are the substances on the existing national Positive Lists in use in France, Germany and the Netherlands, and which had been collated earlier in the "Combined List". The substances on the Combined List can be transferred to the Core List (the 4MSI Positive List of confirmed substances) after they have been reviewed by 4MSI.

Core List (list of confirmed substances)

The 4MS Initiative has agreed procedures for the evaluation of organic substances in use in products in its Common Approach on Organic Materials part A, "Methodologies for Testing and Accepting Starting Substances to be Included in the Positive List", first published in

December 2011, and last revised in August 2020. The Common Approach sets out the process to be followed for the assessment and acceptance of substances. Substances approved by this procedure are included in the "Core List", which is the 4MSI-Positive List of substances. Substances from the Combined List which have been assessed according to the criteria for approval by one of the MS's, and for which the positive opinion was accepted by the other MS's, have been transferred now onto the Core List. The Core List therefore only contains confirmed substances. In addition, substances from the Combined List for which a favourable EFSA opinion was already available, or for which other adequate information was available, have also been transferred onto the Core List. The Core List (list of confirmed substances) is found in Annex A.

Combined List (list of substances under review)

The first version of the Combined List was published in 2011. This was a compilation of substances that appeared on the national lists and which did not appear in the Union List of Regulation (EU) No. 10/2011 (referred to as: "FCM-List of 10/2011"). Pigments and colourants currently permitted in the MS's are not included in the Combined List. The Combined List is periodically updated by removing substances that have been transferred to the Core List or to the List of Obsolete Substances, and by adding substances that were erroneously not included in the version of 2011, or have been evaluated on a national level in the transitional period. The Combined List (3rd revision) is found in Annex B.

Obsolete List (list of obsolete substances)

Substances from the Combined List that are not known to be used anymore in certified or approved PDW's have been transferred onto the 'Obsolete List'. This List is found in Annex C. In situations where it appears that a substance has inadvertently been missclassified as being 'obsolete', then this substance can be returned to the Combined List. Substances that are on the Obsolete List will eventually be deleted.

Actions required by Industry

Should Industry notice substances on the Obsolete List, which they still use in certified or approved products, Industry can inform the relevant MS, making reference to the certificate or approval. The substance will be returned to the Combined List.

In a previous version of this document it was announced that Industry would be asked to submit dossiers for re-evaluation of substances on the Combined-List. However, in the upcoming revision of the European Drinking water Directive, it is stated that harmonised minimum requirements for materials in contact with water have to be established. This would also include the compilation of a European Positive List of starting substances. Pending the developments, the 4MSI will not start a systematic re-evaluation process for substances that are on the Combined List.

Annex A - Core List (list of confirmed substances)

| PM/REF No | CAS No | Name | Use as additive PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification |
|--------------|-----------|--|----------------------------|--|---------------------|--|---|---------------|--|
| - | - | monomers and other starting substances according to plastic regulation 10/2011 | | yes | | monomer | 1/20 SML | , , | Restrictions and specifications as in Reg. (EU) No 10/2011 |
| - | - | additives according to plastic regulation 10/2011 | yes | | | additive | 1/20 SML | 1/20 SML(T) | Restrictions and specifications as in Reg. (EU) No 10/2011 |
| - | - | pigments | | | | pigment | | | - A 0.1 μg/L solution in water, tested on colour, should result in ">10 mg/L Pt/Co", using the same method as is prescribed for measurement of colour in migrationwater, and - Substance has to comply with purity requirements for colorants and pigments |
| - | - | solvents | yes | | | | 0.0001 | | Must be removed during the production process |
| - | - | polymers according to PL's (i.e. all starting substances have to be listed in the PL's that apply to DWP), with a MW above 1000 Da | yes | | | polymeric additive | MTC's of all starting substances apply | | QM/QMA or other limits as in 10/2011 |
| - | 1071-93-8 | adipic acid dihydrazide (#) | | yes | coatings | monomer | 0.0025 0.0001 | | adipic acid dihydrazide hydrazine (CAS 302-01-2); to be checked by analysis (degradation product) Only to be used for powder coatings |
| _ | 9005-82-7 | amylose | yes | | coatings | initiator | | | |
| 37520 | 2634-33-5 | 1,2-benzisothiazol-3(2H)-one | yes | | rubber, silicone | antifoaming, biocide in can preservation | 0.025 | | no antimicrobial effects on the surface of the end product |
| | 119-53-9 | benzoin | yes | | coatings | polymerisation production aids | 0.0025 | | |

| PM/REF No | CAS No | Name | Use as additive PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | |
|--------------|------------|--|----------------------------|--|-----------------------|------------------------|---|---------------|--|
| 38600 | 78-63-7 | 2,5-bis(tert-butylperoxy)-2,5-dimethylhexane (#) | yes | yes | rubber | vulcanisation agent | 0.0001 0.5 0.0001 0.0001 0.0001 0.0001 | | 2,5-bis(tert-butylperoxy)-2,5- dimethylhexane tert-butanol tert-amylalcohol 2,5-dimethyl-hexanediol 2,2,5,5-tetramethyltetrahydrofurane Additionally, if DHBP is used > 0.4%: 3,3,6,6-tetramethyl-1,2-dioxane di-tert-butylperoxide (both impurities of DHBP) |
| _ | 7637-07-2 | boron trifluoride | yes | | plastics, rubber | catalyst | | | MTC(T) expressed as boron; MTC(T) expressed as fluoride |
| 40430 | 109-63-7 | boron trifluoride etherate | yes | | plastics | catalyst | | | MTC(T) expressed as boron; MTC(T) expressed as fluoride |
| 40594 | 75-65-0 | tert-butanol | yes | | platics, coatings | solvent | 0.5 | | |
| - | 25085-50-1 | 4-tert-butylphenol formaldehyde resin (oligomers Mw < 1000 Da: max. 25%; methylol groups: max. 16%) | | yes | rubber | crosslinking agent | 0.0025 0.75 0.050 | | 4-tert butylphenol formaldehyde xylene |
| 41200 | 7789-75-5 | calcium fluoride | yes | | plastics | | | 0.15 | MTC(T) expressed as fluoride |
| - | 8007-24-7 | cashew nut shell liquid, distilled (> 90% cardanol) | , | yes | coatings | hardener | 0.0025 | | not for use as reactive diluent |
| 14450/1 | - | castor oil fatty acids, dehydrated | | | | | | | |
| 14453 | 61790-39-4 | castor oil fatty acids, hydrogenated | | yes | coatings | monomer | | | |
| 14505 | 9004-35-7 | cellulose acetate | | yes | coatings | monomer | | | |
| 14512 | 9004-39-1 | cellulose acetate propionate | | yes | coatings | monomer | | | |
| 43760 | 26172-55-4 | 5-chloro-2-methyl-2H-isothiazol-3-one | yes | | coatings, silicone | | 0.0005 | | only to be used as in-can preservative; no antimicrobial effects on the surface of the end product |
| 43730 | 55965-84-9 | 5-chloro-2-methyl-2H-isothiazol-3-one (CAS 26172-55-4) and 2-methyl-2H-isothiazol-3-one (CAS 2682-20-4), mixture (3:1) | yes | | coatings | in can preservation | 0.0075 | | only to be used as in-can preservative; no antimicrobial effects on the surface of the end product |
| - | 21679-31-2 | chromium(III)acetylacetonate | yes | | plastics | adhesion | | 0.005 | MTC(T) expressed as chromium |
| _ | 10025-73-7 | chromium(III)chloride | yes | | plastics | catalyst | | 0.005 | MTC(T) expressed as chromium |
| _ | 11118-57-3 | chromium oxide | yes | | plastics | catalyst | | 0.005 | MTC(T) expressed as chromium |
| - | 7681-65-4 | copper(I)iodide | yes | | | | | | MTC(T) expressed as iodine MTC(T) expressed as copper |

| PM/REF No | CAS No | Name | Use as additive PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | |
|------------------|------------|--|----------------------------|--|-----------------------------------|--------------------------------------|---|---------------|---|
| 47080 | 110-05-4 | di-tert-butyl peroxide | | yes | plastics, rubber | crosslinker, aids to polymerization, | 0.0001 0.5 | | peroxide tert-butanol |
| 66620 | 75-09-2 | dichloromethane | yes | | plastics, rubber, coatings | vulcanisation agent solvent | 0.015 0.0025 | | methyl tert-butyl ether |
| _ | 80-43-3 | dicumylperoxide ^(#) | yes | yes | rubber | vulcanisation agent | 0.0001 0.0025 0.0001 0.0025 0.0007* | | dicumyl peroxide cumylalcohol methylcumylether alpha-methylstyrene acetophenone * interim MTCtap, an ECHA/CoRAP assessment is ongoing |
| 48030 | 112-34-5 | diethylene glycol monobutyl ether (DEGBE) | yes | | coatings, silicone | solvent | | | MTC(T) for sum of (di)ethyleneglycol, monoalkyl (C1,C2,C4,C6) ethers and acetic acid, 2-ethoxyethyl ester |
| - | 3437-84-1 | diisobutyryl peroxide | yes | | plastics | AtP (initiator) | - 0.0001 0.0025 | | diisobutyryl peroxide; Isopropyl isobutyrate; 2,3-dimethylbutane; - maximum use level: 0.2 %; - only for use in PVC / PVC-C |
| 49160 | 127-19-5 | dimethylacetamide | yes | | plastics | solvent | 0.0025 | | , |
| 56320 | 1323-83-7 | distearic acid, diester with glycerol | yes | | plastics | | | | |
| 53255 | 100-41-4 | ethylbenzene | yes | | platics, coatings, silicone | solvent | 0.03 | | |
| 53600 | 60-00-4 | ethylenediamine tetra acetic acid (EDTA) (#) | yes | | | additive | 0.06 | | MCT(T) for sum of (di)ethyleneglycol,monoalkyl (C1,C2,C4,C6) ethers and acetic acid, 2-ethoxyethyl ester |
| 16993 | 111-76-2 | ethyleneglycol monobutyl ether | yes | yes | coatings, silicone | solvent | | | MCT(T) for sum of (di)ethyleneglycol,monoalkyl (C1,C2,C4,C6) ethers and acetic acid, 2-ethoxyethyl ester |
| 16999 | 112-25-4 | ethyleneglycol monohexyl ether | yes | yes | coatings | solvent | | 0.15 | |
| 17175 | 68938-15-8 | fatty acids, coco hydrogenated | | yes | coatings | monomer | _ | | |
| 18115 / 57520 | 31566-31-1 | glycerol monostearate | yes | yes | rubber, coatings, silicone | processing aid, additive | | | MTC does not need to be verified when process temperature > 100 °C |

| PM/REF No | CAS No | Name | Use as additive PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification |
|-----------------|----------------------------|--|----------------------------|--|------------------------------------|--|------------|---------------|--|
| 59330 | 110-54-3 | n-hexane, incl. structural isomers up to 40% (cyclohexane <3%) EC-No.: 925-292-5 | yes | | | solvent | 0.25 | | |
| _ | 1333-74-0 | hydrogen | yes | | rubber | polymer modifier | | | |
| - | 93685-81-5 (13475-82-6) | isododecane (main isomer: 2,2',4,6.6'-pentamethylheptane) | yes | | plastics | phlegmatiser for organic peroxides | 0.0025 | | |
| 63240 | 8006-54-0 | lanolin (pharmacopeia grade) | yes | | coatings | | | | MTC(T) expressed as chromium, MTC(T) expressed as methacrylic acid |
| - | 25182-44-9 | methacrylic acid, chromium (III) salt | | yes | plastics | aids to polymerization, adhesion promoter for fillers | | 0.005 0.3 | |
| 21827/666 55 | 78-93-3 | methyl ethyl ketone (butan-2-one) (#) | yes | yes | plastics, coatings, silicone | solvent | 0.25 | | |
| 66725 | 108-10-1 | methyl isobutyl ketone (4-methylpentan-2-one) | yes | | platics, coatings, silicone | solvent | 0.25 | | |
| 22190 | 2163-42-0 | 2-methylpropane-1,3-diol | | yes | coatings | monomer | 0.25 | | |
| _ | 7782-44-7 | oxygen | yes | yes | plastics | catalyst | | | |
| - | 27619-97-2 | perfluorohexylethylsulfonic acid | yes | | plasics, coatings | emulsifier | 0.0001 | | |
| - | 1187-93-5 | perfluoromethylperfluorovinylether | | yes | rubber | comonomer | 0.0001 | | QM= 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety |
| 23125 | 103-71-9 | phenyl isocyanate | | yes | coatings | monomer | | ND (<0.0001) | |
| 23173 | 1314-56-3 | phosphoric anhydride | yes | yes | coatings | monomer/ catalyst | | | Only to be used for sintered PTFE coatings |
| 79550 | 9014-85-1 | polyethyleneglycol-2,4,7,9-tetramethyl-5-decyn-4,7-diol ether | yes | | coatings | | | | |
| 80160 | 37349-34-1 | polyglyceryl-5 stearate | yes | | coatings, silicone | | | | |
| - | 9046-10-0 | polyoxypropylene diamine (POPDA) (average Mw≥230 Da; purity: min. 80% POPDA) | | yes | coatings | hardener | 0.0025 | | manufactured by sintering |
| 23680/ 81280 | 9002-89-5 | polyvinyl alcohol | yes | yes | plastics, rubber | emulsion polymerization aid, thickener, solvent | | | |
| _ | 12136-45-7 | potassium oxide | yes | | plastics | other additive | | | |

| PM/REF No | CAS No | Name | Use as additive PPA, or AP | Use as monomer or other starting substance | Material | Technological function | | MTC(T) [mg/l] | Restrictions and specification |
|-----------------|--------------|---|----------------------------|--|------------------------------------|-----------------------------|--------|---------------|---|
| 24440 | 9000-59-3 | shellac | | yes | coatings | monomer | | | The polymer may contain 'siloxane and silicone, dimethyl, hydroxy-terminated (Mw>7400 Da)', fatty acids, and 'C16-C18-fatty acids ester of pentaerythritol' |
| - | 2098907-70-9 | siloxane and silicone, dimethyl, hydroxy- terminated (Mw>7400 Da), ethers with C16-C18-fatty acids esters with pentaerythritol | yes | | rubber | polymeric additive | | | MTC(T) expressed as fluor |
| _ | 7681-49-4 | sodium fluoride | yes | | plastics | antioxidant | | 0.15 | |
| - | 1313-59-3 | sodium oxide | yes | | | | | | Diameter > 1 µm (average diameter 5 30 µm) |
| - | - | stone wool (EC-No. 926-099-9) | yes | | rubber | filler | - | | expressed as SO ₂ |
| - | 7782-99-2 | sulfurous acid | yes | | | additive | | 0.5 | |
| 93420 | 7646-78-8 | tin(IV)chloride | yes | | coatings | | | | the MTC is higher than the odour threshold |
| 93540 | 108-88-3 | toluene | | | rubber, coatings, silicone | dispersive | 0.06 | | |
| - | 101-37-1 | triallylcyanurate | | | rubber | cross linker | 0.0025 | | QM= 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety |
| 25573 | 16938-22-0 | 2,2,4-trimethylhexane-1,6 diisocyanate | | yes | coatings | monomer | | ND (<0.0001) | QM= 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety |
| 25574 | 15646-96-5 | 2,4,4-trimethylhexane-1,6-diisocyanate | | yes | | monomer | | ND (<0.0001) | |
| - | 3048-64-4 | 5-vinyl-2-norbornene | | yes | rubber | comonomer | 0.0025 | | |
| 95870 | _ | wheat protein | yes | | | | | | the MTC is higher than the odour threshold |
| 26370, 95945 | 1330-20-7 | xylene ^(#) | yes | | plastics, coatings, silicone | dispersive agent/solvent | 0.05 | | MTC(T) expressed as zinc |
| 96180 | _ | zinc dust | yes | | coatings | filler | | 0.25 | MTC(T) expressed as zinc |
| 96200 | 55799-16-1 | zinc hydroxyphosphite | yes | | coatings | filler | | 0.25 | MTC(T) expressed as zinc |
| 96240 | 1314-13-2 | zinc oxide | yes | | rubber, lubricants | filler, vulcanisation agent | | 0.25 | |

^(#) Denmark did not contribute to the evaluation

Annex B - Combined List (list of substances under review)

| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|------------------|------------|---|-----------------------------|--|-----------------------------------|--|------------|------------------|---|---------------|
| - | 14024-18-1 | acetylacetonate, iron salt | yes | | plastics | PPA, aids to polymerization | NL: 0.0025 | | DE: max. 0.01 % | DE, NL |
| - | 37187-22-7 | acetylacetone peroxide | yes | | plastics | | 0.0001 | | | NL |
| - | 17501-44-9 | acetyl acetonic acid, zirconium salt | yes | | silicone | catalyst- hardener | | | DE: [1] | DE |
| - | - | acrylic acid, esters with alcohols, monohydric, aliphatic, saturated, C1-C18 | | yes | coatings | monomer | 0.3 | | MTC expressed as acrylic acid | NL |
| - | - | addition products of trivinylcyclohexane and alpha, omega-dihydrogen-polyhydrogenmethyldimethyl-siloxanes | | yes | silicone | monomer | | | DE: maximum quantities 10 % [1] | DE |
| 32920 | - | adipic acid, esters with alcohols, monohydric, aliphatic, primary, saturated, (C6-C12) | yes | yes | plastics | plasticizer | | | | NL |
| 12520 | _ | alkadienes (C3-C8) | | yes | coatings | monomer | | | QM = 1 mg/kg in EP | NL |
| | | alkoxysilanes with functional groups, e.g. vinyl, methacryl, amino or glycidyl groups | yes | | plastics | adhesion promoters for fillers | | | max. 0.5 %, based on the filler, or max. 0.3%, based on the plastic component | DE |
| | | alkylarylsulfonic acid | yes | | plastics | emulgator | | | DE: max. 3% | DE |
| | 63449-41-2 | alkyl(C8-C18)dimethylbenzylammonium chloride | yes | | lubricants | | | | | DE |
| I | ı | alkyl(C8-C18)benzene sulfonates, sodium salts | | yes | rubber | emulsifier | | 1.5 | MTC(T) for the sum of sodium salts of alkyl(C8-C18)benzene sulfonates, alkyl(C8-C18)naphthalene sulfonates, alkyl(C8-C18)sulfates and alkyl(C8-C18)sulfonates | FR, NL |
| _ | 1 | alkyl(C8-C18)naphthalene sulfonates, sodium salts | | yes | rubber | emulsifier | | 1.5 | MTC(T) for the sum of sodium salts of alkyl(C8-C18)benzene sulfonates, alkyl(C8-C18)naphthalene sulfonates, alkyl(C8-C18)sulfates and alkyl(C8-C18)sulfonates | FR, NL |
| 1 | | alkyl(C1-C8)-silicic acid or orthosilicic acid with aliphatic monohydric alcohols (C2-C4) and the monomethyl ether of ethanediol (methylglycol) and their condensation products, esters of | | yes | silicone | crosslinking agent | | | max. use level 3 % [1] | DE |
| | 54326-11-3 | aluminium hydroxide benzoate stearate | | yes | lubricants | thickener | | | | DE |
| 34800 | _ | amide of aliphatic carboxylic acids, C8-C22 | yes | | silicone | emulgator | | | DE: max. use level 1.5% [1] | DE, FR |
| 34960 | _ | 3-aminocrotonic acid, esters with butyleneglycol | yes | | coatings | | | | | FR |
| 35040 | 1 | 3-aminocrotonic acid, esters with mono- or dihydric alcohols | yes | | coatings | | | | | FR |
| ı | 1760-24-3 | [3-(2-aminoethyl)aminopropyl]trimethoxysilane | yes | yes | plastics, coatings | | 0.0001 | | | NL |
| ı | 78-67-1 | 2,2'-azobis(isobutyronitrile) | yes | | plastics | initiator | | | DE: use max. 0,2 % | DE, NL |
| 38600 | 78-63-7 | 2,5-bis(tert-butylperoxy)-2,5-dimethylhexane | yes | | plastics coatings, silicone | aids to polymerization (crosslinker) | 0.0001 | | | DE, FR, NL |
| - | 1068-27-5 | 2,5-bis(tert-butylperoxy)-2,5-dimethyl-3-hexyne | yes | yes | plastics | aids to polymerization | 0.0001 | | | DE, NL |

| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|------------------|--|---|-----------------------------|--|-----------------------|---|-------------------------------------|------------------|--|---------------|
| 38615 38625 | 25155-25-3 {2212-81-9 & 2781-00-2} | 1,3-(and/or 1,4)-bis(tert-butylperoxyisopropyl)benzene | | yes | plastics, rubber | vulcanisation agent, aids to polymerization | 0.0001 | | DE: not for rubber | DE, FR, NL |
| 39920 | 85-60-9 | bis(2-methyl-4-hydroxy-5-tert-butylfenyl)butane | yes | | rubber | antioxidant | 0.015 | | | NL |
| - | 101-67-7 | bis(4-octylphenyl)amine; (= 4,4'-dioctyldiphenylamine) | yes | | rubber | aging protection products | 0.0025 | | | NL |
| 12974 | 1675-54-3 | bisphenol-A-diglycidylether (BADGE) (= 2,2-bis(4-hydroxyphenyl)propane bis(2,3-epoxypropyl) ether) | | yes | coatings | resin | 0.45 0.05 0.0025 0.0001 | | BADGE and its hydrolysis products BADGE chlorohydrins bisphenol A epichlorohydrine | DE, NL |
| 12976 | 39817-09-9 | bisphenol-F-diglycidylether (BFDGE) (= bis(hydroxyphenyl)methane bis(2,3-epoxypropyl) ethers) | | yes | coatings | resin | 0.0025 0.0025 0.0001 0.006 | | BFDGE and its hydrolysis products bisphenol F epichlorohydrine 3-monochloro-propane-1,2-diol | DE, NL |
| - | 1338-23-4 | 2-butanone peroxide | yes | yes | plastics | PPA, crosslinker | 0.0001 | | | NL |
| _ | 95-31-8 | N-tert-butyl-2-benzothiazolesulfenamide | | yes | rubber | crosslinking agent | | | | FR |
| 40640 | 98-29-3 | 4-tert-butylcatechol | yes | | coatings, silicone | | | | | FR, NL |
| - | 3457-61-2 | tert-butylcumylperoxide | yes | | coatings, silicone | aids to polymerization | | | DE: no peroxide on the product surface [1] | DE, FR |
| - | 17540-75-9 | 4-sec-butyl-2,6-di-tert-butylphenol | yes | | plastics, rubber | processing excipient, antioxidant | NL: 0.0025 | | | NL |
| - | 2372-21-6 | tert-butylperoxy isopropyl carbonate | yes | | plastics | PPA, aids to polymerization | 0.0001 | | max. 0.5 % | DE |
| - | 88-18-6 | 2-tert-butylphenol | | yes | plastics, coatings | | 0.0001 | | | NL |
| 42080 | 1333-86-4 | carbon black | yes | | | filler | | | toluene extractables: maximum 0.15%, determined according to ISO method 6209 | NL |
| 42240 | - | carbon fibers | yes | | | filler | | | | FR |
| - | - | Condensation products of ethylene oxide with alcohols (C3-C18), phenolalkyl (C4-C9), and their sulphonated, sulphurated or phosphated derivated | | yes | rubber | | | | | FR |
| 14877 | 2556-36-7 | 1,4-cyclohexanediisocyanate | | yes | coatings | monomer | | ND (<0.0001) | QM = 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety | DE |
| | | cyclic organopolysiloxane with methylgroups, alone or n-alkyl (C2-C32)-group | | yes | lubricants | basic oil | | | DE: [1] | DE |
| - | 694-83-7 | cyclohexane-1,2-diamine | | yes | coatings | monomer, crosslinking agent | 0.0025 | | | DE |

| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|------------------|-------------|--|-----------------------------|--|------------------------------------|--|--------------------------------------|------------------|--|---------------|
| - | 95-33-0 | N-cyclohexyl-benzothiazole-2-sulfenamide | yes | yes | rubbers | crosslinking agent | 0.1 100 | | N-cyclohexyl-benzothiazole-2-sulfenamide; 2-mercaptobenzothiazole (provisional value); Reaction-/degradation products: | DE, FR, NL |
| | | | | | | | 0.0025 0.0001 0.0001 0.0025 | | 2,2'-dithio(bis)benzothiazole; benzothiazole; 2-benzothiazolone; cyclohexylamine | |
| - | 17796-82-6 | N-(cyclohexylthio)phthalimide | yes | | rubber | accelerator | 0.15 | | | NL |
| - | 80-15-9 | cumene hydroperoxide | yes | yes | plastics, coatings | initiator, catalyst | 0.0001 | | | NL |
| 13250 | 101-77-9 | 4,4'-diaminodiphenylmethane | yes | yes | coatings | monomer | 0.0001 | | | DE, FR, NL |
| - | 68953-84-4 | N,N'-diaryl-p-phenylenediamine | yes | | rubber | | 0.0001 | | | NL |
| 46440 | 94-36-0 | dibenzoyl peroxide | | yes | plastics, rubber, silicone | aids to polymerization, vulcanisation agent | 0.0001 | | DE: not for rubber | DE, FR, NL |
| - | 111-92-2 | di-n-butylamine | yes | | plastics | aids to polymerization, pH-regulator | 0.001 | | | DE, NL |
| 47060 | 171090-93-0 | 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionic acid, esters with linear or branched alcohols (C13-C15) | yes | | rubber | antioxidant | 0.0025 | | | DE |
| - | 6731-36-8 | 1,1-di-tert-butylperoxy-3,3,5-trimethylcyclohexane | yes | yes | plastics, rubber | initiator, crosslinking agent | 0.0001 | | | NL |
| 47220 | 77-58-7 | dibutyltin dilaurate | yes | | plastics, coatings, silicone | catalyst | NL: ND | | | DE, FR, NL |
| _ | ı | α,ω-dicarboxylic acids (C6-C12), aliphatic, unbranched | | yes | | monomer | | | | NL |
| _ | 133-14-2 | 2,4-dichlorobenzoyl peroxide | | yes | coatings, silicone | crosslinking agent | 0.0001 | | DE: [1] | DE, FR, NL |
| _ | 80-43-3 | dicumylperoxide | yes | yes | plastics | aids to polymerization (crosslinker) | 0.0001 | | | DE, FR, NL |
| 15730 | 77-73-6 | dicyclopentadiene | | yes | rubber | monomer | NL: 0.0025 | | | NL |
| 48050 | 111-90-0 | diethyleneglycol monoethyl ether | yes | | coatings | solvent | | 0.15 | MTC(T) for the sum of all of glycolmonoalkylethers | DE |
| - | 140-01-2 | diethylenetriaminepentaacetic acid pentasodium salt | yes | | plastics | dispersive agent | | | | NL |
| - | 3710-84-7 | N,N-diethylhydroxylamine (impurities: diethylamine: max. 0.1%; N-nitrosodiethylamine: max 0,5 mg/kg) | yes | | plastics | | | | DE: max. use 0.02% | DE, NL |
| - | 1047-16-1 | 5,12-dihydroquino(2,3-b)acridine-7,14-dione | yes | | plastics, coatings | pigment | | | | NL |
| - | 105-74-8 | dilauroyl peroxide | yes | | plastics | initiator | | | DE: [1] | DE |
| | | | | | • | | | | | |

| | | | Use as | Use as | | | | | | |
|------------------|------------|--|----------------------------|-------------------------------------|-----------------------|--|------------|------------------|---|---------------|
| PM/ REF No | CAS No | Name | additive, PPA, or AP | monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
| _ | 109-87-5 | dimethoxymethane | yes | yes | plastics | monomer, aids to polymerisation | 1 | | | DE, FR, NL |
| 49225 | 124-40-3 | dimethylamine | | yes | rubber, coatings | monomer | 0.003 | | DE: not for rubber | DE, FR |
| 16150 / 49235 | 108-01-0 | dimethylaminoethanol | yes | | plastics, coatings | | 0.9 | | | DE, FR |
| _ | 7005-47-2 | 2-dimethylamino-2-methyl-1-propanol | yes | | plastics | | | | | FR |
| - | 895-85-2 | di(4-methyl-benzoyl)peroxide | | yes | silicone | vulcanisation agent, crosslinking agent | | | | DE |
| - | 115-10-6 | dimethyl ether | yes | | coatings | propellant | <0.001 | | | DE |
| 49465 | 68-12-2 | N,N-dimethylformamide | yes | | plastics, coatings | solvent | 0.025 | | | NL |
| - | 29240-17-3 | (1,1-dimethylpropyl) 2,2-dimethyl-propaneperoxoate | yes | | plastics | PPA, aids to polymerization | 0.0001 | | max. 0.2% | DE |
| - | 68928-76-7 | dimethyltin dineodecanoate | yes | | plastics | PPA, aids to polymerization | | | for sum of dimethyltin containing compounds DE: max. 0.12% | DE |
| - | 70131-67-8 | dimethylsiloxane, hydroxy terminated | | yes | rubber, lubricants | basic oil | | | DE: [1] | DE |
| 50080 | 3806-34-6 | dioctadecyl pentaerythritol diphosphite | yes | | plastics | stabilizer | | | | FR, NL |
| - | 3851-87-4 | di-(3,5,5-trimethyl)-hexanoyl)peroxide | yes | | plastics | aids to polymerization | 0.0001 | | DE: max. 0.2% | DE |
| - | 971-15-3 | di-N-pentamethylenethiuram hexasulfide | yes | | rubber | accelerator | | 0.05 | MTC(T) in this specific case means that the restriction shall not be exceeded by the sum of the migration levels of all di-N-pentamethylenethiuram sulfides | FR, NL |
| _ | 120-54-7 | di-N-pentamethylenethiuram tetrasulfide | yes | | rubber | accelerator | | 0.05 | MTC(T) in this specific case means that the restriction shall not be exceeded by the sum of the migration levels of all di-N-pentamethylenethiuram sulfides | FR, NL |
| - | 122-39-4 | diphenylamine | yes | | plastics, rubber | catalyst | | | max. use level 0.1% | NL |
| _ | 68411-46-1 | diphenylamine, octylated | yes | | rubber | anti-ageing | | | QM = 1.5% | FR |
| 51500 | 102-06-7 | N,N-diphenylguanidine | | yes | rubber | crosslinking agent | NL: 0.0025 | | | NL |
| 46400 | 120-78-5 | dithiobis(2-benzothiazole) / dibenzothiazyldisulfide | | yes | rubber | crosslinking agent | | NL: 0.15 | MTC(T) for the sum of dithiobis(2-benzothiazole), 2,2'-dibenzothiazyl disulfide, mercaptobenzothiazole, and 2-(4-morpholino)thiobenzothiazole | FR, NL |
| - | 25103-58-6 | tert-dodecanethiol | yes | | plastics | PPA, aids to polymerization | | | max. 0.7% | DE |
| 16920 | 87057-87-2 | 2-ethylbutane-1,4-diisocyanate | | yes | coatings | monomer | | ND (<0.0001) | QM= 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety | DE, FR |

| | | Combined List for S | | | | | | | | |
|------------------|------------|--|-----------------------------|--|-----------------------|----------------------------|---------------------------------------|---------------------------------------|--|---------------|
| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
| 16996 | 110-80-5 | ethyleneglycol monoethyl ether | yes | yes | coatings, silicone | monomer, solvent/dluter | | 0.15 | MTC(T) for sum of (di)ethyleneglycol monoalkyl (C1,C2,C4,C6) ethers and acetic acid, 2-ethoxyethyl ester | DE |
| 17002 | 109-86-4 | ethyleneglycol monomethyl ether | yes | yes | coatings | solvent/diluter | | 0.15 | MCT(T) for sum of (di)ethyleneglycol monoalkyl (C1,C2,C4,C6) ethers and acetic acid, 2-ethoxyethyl ester | DE |
| 54120 | 149-57-5 | 2-ethylhexanoic acid | yes | | plastics | stabilizer, lubricant | 0.0025 | | | DE, FR, NL |
| - | 94-96-2 | 2-ethyl-1,3-hexanediol | | yes | plastics, coatings | monomer | 0.0025 | | | NL |
| - | 22208-25-9 | 2-ethyl-2-(hydroxymethyl)-1,3-propanediol triacetoacetate | | yes | coatings | monomer, crosslinker | 0.3 | 0.0025 | for the sum of 2-ethyl-2-(hydroxy-methyl)-1,3- propanediol (mono-, di- and tri-)acetoacetates; Reaction products: 1,1,1-trimethylol propane | DE |
| - | 17689-77-9 | ethyltrisacetoxysilane | | yes | silicone | crosslinking agent | | | DE: [1] | DE |
| _ | 28106-30-1 | ethylvinylbenzene | yes | | plastics | | | 0.0001 | MTC(T) for the sum of ethylvinylbenzene and divinylbenzene (FCM No. 405) | NL |
| _ | 78-27-3 | ethynylcyclohexanol | yes | | coatings, silicone | solvent | | | DE: [1] | DE, FR |
| _ | _ | fatty acids (unbranched, saturated and unsaturated, with an even number of carbon atoms, C8-C22, with a maximum content of 2% unsaponifiable matter), as compounds with bis(2-hydroxyethyl)amine | yes | yes | plastics | antistatic, lubricant | 1.5 | | | NL |
| _ | - | fatty acids (unbranched, saturated and unsaturated, with an even number of carbon atoms, C8-C22, with a maximum content of 2% unsaponifiable matter), amides of. | yes | yes | plastics, rubber | lubricant, activator | | | | NL |
| _ | _ | fatty acids (unbranched, saturated and unsaturated, with an even number of carbon atoms, C8-C22, with a maximum content of 2% unsaponifiable matter), esterified with alcohols, monohydric, primary, unbranched, saturated, C4-C18, as well as oleyl alcohol | yes | yes | plastics | lubricant | | | | NL |
| _ | - | fibers, natural and synthetic, with the exception of asbestos | yes | | coatings | filler | | | | FR, NL |
| 13160 22552 | 9003-36-5 | formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol (Novolak glycidyl ether, NOGE) * | yes | yes | coatings | monomer | 0.0025 0.0025 0.0001 0.006 | | NOGE bisphenol F epichlorohydrin 3-monochloro-propane-1,2-diol Only to be used in powder coatings | DE, NL |
| 54970 | 9003-08-1 | formaldehyde-2,4,6-triamino-1,3,5-triazine, copolymer | yes | | coatings | | | | DE: only sintered PTFE | FR |
| _ | 9006-24-0 | formaldehyde-xylene, copolymer | yes | | rubber | resin | | | | FR |
| - | _ | glycerol esters with linear fatty acids satured or not with an even number of carbon C8-C20 and/or adipic acid, citric acid, oxystearin acid and ricinoleic acid | yes | | coatings | | | | | FR |
| 18370 | 592-45-0 | 1,4-hexadiene | | yes | rubber | monomer | | 0.0006 | MTCtap as sum for 1,4 and 1,5 hexadiene | NL |
| | | | | | | | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | |

| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|------------------|-------------|---|-----------------------------|--|-----------------------|------------------------|------------|----------------------|--|---------------|
| 18400 | 592-42-7 | 1,5-hexadiene | | yes | rubber | monomer | | 0.0006 | MTCtap as sum for 1,4 and 1,5 hexadiene | FR |
| _ | 16096-31-4 | 1,6 hexanediol diglycidyl ether | yes | | coatings | | 0.0001 | | | FR, NL |
| - | - | hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, with EC No. 920-750-0, boiling point 90 to 165 °C, log Po/w=2.2-5.2, insoluble in water | yes | | | solvent | | | only to be used if the production process temperature is above the boiling point | DE |
| - | _ | hydrocarbons, C7-C9, isoalkanes, with EC No. 921-728-3, boiling point 90 to 150°C, negligible solubility in water | yes | | | solvent | | | only to be used if the production process temperature is above the boiling point | DE |
| - | | hydrocarbons, C10-14, aromatic content ≤1%, | yes | | plastics, coatings | solvent | | | only to be used if the production process temperature is above the boiling point | NL |
| - | 7722-84-1 | hydrogen peroxide | yes | | plastics, coatings | aids to polymerization | 0.0001 | | DE: max. 0.5 % in final product | DE |
| - | - | 2-hydroxy-2-sulfinato acetic acid, disodium salt (35-60%), 2-hydroxy-2-sulfonato acetic acid, disodium salt (10-60%) and sodium sulfite (0-40%) (mixture) | | yes | plastics | aids to polymerization | | | max use level of 0.5% | DE |
| - | 2226-96-2 | 4-hydroxy-2,2,6,6-tetramethylpiperidinoxyl | yes | | plastics | blocking agent | NL: 0.0025 | | DE: [1] | DE, NL |
| 62210 | 55406-53-6 | 3-iodo-2-propynylbutylcarbamate | yes | | rubber, coatings | accelerator | | | | FR |
| 62255 | 75-28-5 | isobutane | yes | | lubricants | | | | | FR |
| 18970 | 78-83-1 | isobutanol | yes | | silicone | solvent | | | DE: [1] | DE |
| - | 7425-80-1 | isobutyl titanate | yes | | silicone | catalyst | | | DE: [1] | DE, FR |
| 64000 | 3999-01-7 | linoleamide | yes | | coatings, silicone | catalyst | | | DE: [1] | DE, FR |
| 65768 | 149-30-4 | 2-mercaptobenzothiazole | yes | | rubber | accelerator | | NL: 0.15, DE: 0.1 | MTC(T) for the sum of dithiobis(2-benzothiazole), 2,2'-dibenzothiazyl disulfide, mercaptobenzothiazole, and 2-(4-morpholino)thiobenzothiazole; DE: additional requirements to S-crosslinking [2] | DE, FR, NL |
| 19977 | 60-24-2 | 2-mercaptoethanol | yes | | plastics, rubber | other add. | 0.0025 | | | NL |
| _ | 68440-24-4 | mercaptoethyl tallate | yes | | plastics | | 1.5 | | | NL |
| - | - | methacrylic acid, esters with alcohols, monohydric, aliphatic saturated, C1-C18 | | yes | rubber | monomer | 0.3 | | expressed as methacrylic acid | NL |
| - | 115-19-5 | methyl-2-butyn-3-ol-2 | yes | | coatings, silicone | inhibitor | | | DE: [1] | DE, FR |
| 21754 | 15520-10-2 | 2-methyl-1,5-diaminopentane | | yes | coatings | hardener | 0.005 | | | DE |
| - | 7786-17-6 | 2,2-methylenebis(4-methyl-6-nonylphenol) | yes | | plastics, rubber | antioxidant | 0.0001 | | | FR, NL |
| 21823 | 598-09-4 | methylepichlorhydrin | | yes | coatings | monomer | 0.0001 | | | DE |
| _ | 96-29-7 | methyl ethyl ketone oxime | yes | | coatings | blocking agent | NL: 0.12 | | DE: only for hot curing coatings | DE, NL |
| 66715 | 693-98-1 | 2-methylimidazole | yes | | coatings | additive | 0.0025 | | | DE |
| _ | 534-26-9 | 2-methylimidazoline | yes | | coatings | | 0.0001 | | | NL |
| 22065 | 34813-62-2 | 2-methylpentane-1,5-diisocyanate | | yes | coatings | monomer | | ND (<0.0001) | QM= 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety | DE |
| _ | 201687-58-3 | methyltin-2-mercaptoethyl tallate | yes | | plastics | | 0.009 | | | NL |
| - | 4253-34-3 | methyltrisacetoxysilane | | yes | silicone | crosslinking agent | | | DE: [1] | DE |

| PM/ | | Combined List for S | Use as additive, | Use as monomer or | | Technological | | MTC/T) | | |
|-----------|----------------------------|--|------------------|--------------------------|-----------------------|-----------------------------------|------------|--------|--|---------------|
| REF No | CAS No | Name | PPA, or AP | other starting substance | Material | function | MTC (mg/l) | [mg/l] | Restrictions and specification | Auth. MS |
| _ | - | methyltrisbutanoximosilane | | yes | silicone | crosslinking agent | | | DE: [1] | DE |
| - | _ | methyltriscyclohexylaminosilane | | yes | silicone | crosslinking agent | | | DE: [1] | DE |
| - | _ | methyltris-secbutylaminosilane | | yes | silicone | crosslinking agent | | | DE: [1] | DE |
| _ | _ | mono- and/or polytitanic acid, butyl ester (butyltitanate, butylpolytitanate), as necessary, with the monoethylether of ethanediol (ethyleneglycol) in the ratio 1:1 | | yes | silicone | aids to polymerization | | | DE: [1] | DE |
| 67280 | 108-90-7 | monochlorobenzene | yes | | plastics, coatings | | 0.001 | | | FR, NL |
| - | - | mono-n-octyltin tris(maleic acid half ester), prepared with C1-C18, primary, unbranched, saturated alcohols | | yes | plastics | stabilizer, antioxidant | | 0.06 | expressed as tin; sum of mono-n-octyltin-compounds | NL |
| - | - | mono-n-octyltin tris[monoalkyl(C1-C18) maleate] | yes | | plastics | stabilizer, antioxidant | | 0.06 | expressed as tin; sum of mono-n-octyltin- compounds | NL |
| 67840 | - | montanic esters with ethylene glycol and/or 1,3- butanediol and/or glycerol | yes | | plastics | | | | 1 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 | NL |
| - | 51240-95-0 / 64742-48-9 | neodecaneperoxoic acid, 1,1,3,3-tetramethylbutyl ester | yes | | plastics | initiator | 0.0001 | | max use: 0.06% [1] | DE |
| _ | 9084-06-4 | naphtalene sulfonic acid-formaldehyde condensation product, sodium salt | yes | | plastics rubber | emulgator | | 0.0001 | only sintered products DE: not for rubber | DE, FR, NL |
| 68140 | 7697-37-2 | nitric acid | yes | | plastics, coatings | anticrusting, pH regulator | 0.005 | | | FR |
| _ | 26530-20-1 | 2-octyl-2H-isothiazole-3-one | yes | | rubber | preservative | | | | FR |
| 69848 | _ | organopolysiloxanes, containing methylgroups on each silicon atom which can be partially replaced by alkenyl(C2-C32)groups, alkyl (C2-C32)groups, hydroxylgroups, hydrogen, disubstituted alkylamines and/or hydroxylated alkylgroups, acetoxy and/or alkoxy groups and their condensation products with polyethyleneglycol and/or polypropyleneglycol, fluorinated alkylgoups, and phenylgroups | yes | yes | coatings, silicone | monomer, polymeric additive | | | | FR |
| _ | _ | organopolysiloxanes, linear and branched, with methyl groups alone and/or n-alkyl(C2-C32)-, and/or phenyl*, and/or vinyl-, and/or hydroxyl-, and/or alkoxy(C1-C4)-, and/or hydrogen-, and/or carboalkoxyalkyl(-(CH2)2-17-C(O)-O-(CH2)0-17CH3)-, and/or hydroxyalkyl(C1-C3)-groups | yes | yes | silicone | monomer, polymeric additive | | | DE: [1] * may not contain cyclic polysiloxanes that beside the phenyl group bear an hydrogen atom or a methyl group at the same silicon atom | |
| _ | _ | organopolysiloxanes, linear or branched, as mentioned PM/REF No. 69848, but in addition with up to max. 5 % hydrogen and/or alkoxy(C2-C4) and/or carboalkoxyalkyl (-(CH2)2-17-C(O)-O-(CH2)0-17CH3)- and/or hydroxyalkyl(C1-C3) groups attached to the silicon atom | yes | yes | silicone | monomer, polymeric additive | | | DE: [1] | DE |

| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|------------------|--|--|-----------------------------|--|-------------------------|-----------------------------------|------------|------------------|--|----------|
| _ | _ | organopolysiloxanes,linear or branched and/or cyclic*, with methyl groups alone and/or with n-alkyl(C2-C32), phenyl* and/or hydroxyl groups attached to the silicon atom, and their condensation products with polyethylene and/or polypropyleneglycol | yes | yes | silicone | monomer, polymeric additive | | | DE: [1] * may not contain cyclic polysiloxanes that beside the phenyl group bear an hydrogen atom or a methyl group at the same silicon atom | |
| - | 68083-14-7 73138-88-2 68440-81-3 | organopolysiloxanes, linear or branched with methyl- or phenylgroups | | yes | plastics, lubricants | basic oil | | | DE: [1] | DE |
| 76721 | 9016-00-6 63148-62-9 68037-74-1 | organopolysiloxanes, linear or branched with methylgroups | yes | yes | plastics, lubricants | basic oil, anti- foaming agent | | | DE: [1] | DE, NL |
| _ | - | organopolysiloxanes with vinyl groups attached to the silicon atom | yes | yes | silicone | monomer, polymeric additive | | | DE: [1] | DE |
| - | - | oxides and hydroxides of aluminium, magnesium, silicon, titanium and zinc | yes | | | filler | | | | NL |
| 71120 | 8012-95-1 8042-47-5 | paraffin oil | yes | | plastics, rubber | | | | | FR |
| _ | _ | paraffin, solid, including synthetic paraffin | | yes | plastics, rubber | lubricant, plasticizer | | | ultraviolet light absorption of the paraffin meets the requirements | NL |
| _ | 614-45-9 | peroxybenzoic acid, tert-butyl ester | yes | | plastics, coatings | | 0.0001 | | | NL |
| _ | 15520-11-3 | peroxydicarbonic acid, bis(4-tert-butylcyclohexyl) ester | yes | | plastics, coatings | initiator | 0.0001 | | DE: [1] | DE, NL |
| _ | 16111-62-9 | peroxydicarbonic acid, bis(2-ethylhexyl) ester | yes | | plastics | initiator | 0.0001 | | DE: [1] | DE, NL |
| - | 26322-14-5 | peroxydicarbonic acid, dicetyl ester | yes | | plastics | initiator | 0.0001 | | DE: [1] | DE, NL |
| - | 53220-22-7 | peroxydicarbonic acid, dimyristyl ester | yes | | plastics | initiator | 0.0001 | | DE: [1] | DE, NL |
| 72048 | 7727-21-1 | peroxydisulfuric acid, dipotassium salt | yes | | plastics | initiator | 0.0001 | | DE: [1] | DE, NL |
| _ | 7775-27-1 | peroxydisulfuric acid, disodium salt | yes | | plastics | initiator | 0.0001 | | | NL |
| _ | 3006-82-4 | peroxy-2-ethylhexanoic acid, tert-butyl ester | yes | | plastics, rubber | initiator | 0.0001 | | DE: not for rubber | DE, NL |
| _ | 26748-41-4 | peroxyneodecanoic acid, tert-butyl ester | yes | | plastics | | 0.0001 | | | NL |
| _ | 927-07-1 | peroxypivalic acid, tert-butyl ester | yes | | plastics | | 0.0001 | | | NL |
| _ | 13122-18-4 | peroxy(3,5,5-trimethylhexanoic acid), tert-butyl ester | yes | | plastics | initiator | 0.0001 | | | DE, NL |
| 72081/ 10 | - | petroleum hydrocarbon resins (cyclopentadiene type), hydrogenated | yes | | rubber | resin, additive | FR: 0.15 | | | DE, FR |
| _ | 64741-56-6 | petroleum residues, vacuum distilled | yes | | rubber | resin | | | | FR |
| _ | 92062-05-0 | petroleum residues, thermal cracked vacuum | yes | | rubber | resin | | | | FR |
| _ | 68610-06-0 | phenols, butylated, isobutylated or octylated | yes | | rubber | antioxidant | | | | FR |
| _ | 61788-44-1 | phenols, styrenated | yes | | rubber, coatings | antioxidant | | | DE:not for rubber | DE, FR |
| - | 618-36-0 3886-69-9 2627-86-3 | 1-phenylethyl-1-amine | | yes | coatings | monomer, crosslinker | 0.0001 | | | DE |
| - | | 2-phenyl-2-imidazoline | | yes | coatings | hardener | 0.0025 | | | DE |

| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|------------------|------------------|---|-----------------------------|--|-----------------------|-----------------------------------|------------|------------------|---|----------|
| 23060 | 104-49-4 | 1,4-phenylene diisocyanate | | yes | coatings | hardener | | ND (<0.0001) | QM = 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety | DE |
| _ | 7774-80-3 | phenyl-o-tolyl-phenylenediamine | yes | | rubber | protecting agent | 0.0001 | | | NL |
| 73680 | 126-73-8 | phosphoric acid, tributyl ester | yes | | rubber | antifoaming | | | | FR |
| _ | 10294-56-1 | phosphorous acid | yes | | rubber | antioxidant | | | | NL |
| _ | 54771-30-1 | phosphorous acid, dinonylphenyl bis(nonylphenyl) ester | yes | | plastics | plasticizer | 0.3 | | | FR, NL |
| 74960 | 84-61-7 | phthalic acid, dicyclohexyl ester | yes | | plastics | plasticizer, pigment batches | 0.3 | | | DE, FR |
| _ | 110-85-0 | piperazine | yes | | plastics | monomer | 0.075 | | DE: will be deleted in coatings | DE, NL |
| _ | - | platinum complexes | yes | | silicone | catalyst | | | DE: [1] | DE, FR |
| 76461 | 9003-01-4 | polyacrylic acid | yes | | rubber | | | | | FR |
| 76520 | 9003-29-6 | polybutene | yes | yes | rubber, lubricants | antifoaming, basic oil | | | | DE, FR |
| 76530 | 68937-10-0 | polybutene, hydrogenated | | yes | lubricants | basic oil | | | | DE |
| - | _ | polyalcoxyesters of acids, fatty with an even number of carbon (C8-C24) | yes | | plastics | | | | | FR |
| 76680 | 68132-00-3 | polycyclopentadiene | yes | | plastics | resin | | | | FR |
| 76685 | 68037-01-4 | poly 1-decene hydrated | | yes | lubricants | basic oil | | | impurities of hydrocarbons with number of Carbon smaller than 30 not more than 1.5 %, free of naphthene, aromatics and PAH | DE |
| 76690 | ı | polydienic resin, synthetic | | yes | | monomer | | | | FR |
| - | - | polydimethyl siloxanes and polydimethyl silicones, 3- aminopropyl-group terminated, polymers with 1- isocyanato-3-isocyanatomethyl-3,5,5- trimethylcyclohexane | yes | yes | silicone | monomer, polymeric additive | | | DE: [1] Specific restrictions for 1-isocyanato-3-isocyanatomethyl-3,5,5-trimethylcyclohexane and 1-amino-3-aminomethyl-3,5,5-trimethylcyclohexane according 10/2011 | DE |
| - | I | polydimethyl siloxanes and polydimethyl silicones, 3- aminopropyl-group terminated, polymers with bis(4-isocyanatocyclohexyl)methane | yes | yes | silicone | monomer, polymeric additive | | | DE: [1] Specific restrictions for bis(4- isocyanatocyclohexyl)methane and bis(4- aminocyclohexyl)methane according to 10/2011 | DE |
| - | | polyethylene glycol ethers of monohydric aliphatic alcohols (C12-C20) and of alkylphenols (C2-C9) | yes | | silicone | | | | DE: [1] | DE |
| - | - / 9002-98-6 | polyethyleneamine and polyethyleneimine | yes | | coatings | | | | | FR |
| _ | | polyethylene aminostearamide ethylsulfate | yes | | coatings | | | | | FR |
| _ | 28208-80-2 | poly(ethylene-co-acrylic acid), zinc salt | | yes | plastics | | | | | FR |
| 77360 | 9005-07-6 | polyethyleneglycol dioleate | yes | | coatings | additive | | | | DE |
| - | _ | polyethylene oxide (8-14), esterified with lauric acid, oleic acid, ricinoleic acid and/or stearic acid | yes | | | | | | | NL |
| - | - | polyethylene oxide, molecular weight > 200 (pEO) | yes | | plastics | lubricants, other add. | | | | NL |
| - | I | polyethylene oxide(4-14)ether of octyl- and/or nonylphenol | yes | | plastics, rubber | emulgator | 0.25 | | | NL |
| - | - | polyethylene oxide(4-14)ethers of monohydric, primary, unbranched, saturated C12-C18 alcohols | yes | | plastics | plasticizer | 0.25 | | | NL |

| | | | | <u> </u> | | | | | | |
|------------------|------------|---|-----------------------------|--|-----------------------|-------------------------------------|------------|------------------|--|----------|
| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
| 80360 | 9003-27-4 | polyisobutene | yes | yes | rubber, lubricants | polymeric additive, basic oil | | | composition according CR (EU) No. 10/2011, molecular weight >1000Da | DE, FR |
| - | - | polypropylene oxide, esterified with lauric acid, oleic acid, ricinoleic acid and/or stearic acid | yes | | | | | | | NL |
| _ | _ | polysaccharides | yes | | rubber | thickener | | | | FR |
| - | - | poly(styrene-co-maleic anhydride) | yes | | plastics | | | | | FR |
| _ | 9003-53-6 | polystyrene (with pentane as expansion agent) | yes | | rubber | resin | | | | FR |
| 81120 | _ | polyterpenes | yes | | lubricants | | | | | DE, FR |
| 81160 | 9002-84-0 | polytetrafluoroethylene | yes | | lubricants, coatings | polymeric additive | 0.0025 | | MTC for the residual tetrafluoroethylene | DE |
| 95726 | 25213-24-5 | polyvinyl alcohol, manufactured by saponification of polyvinyl acetate, with a degree of saponification >=20% | yes | | plastics | suspending agent | | | max. use: 1% | DE |
| _ | - | polyvinyl alcohol, partially acetylated with < 20% acetyl groups and a K-value of > 40 | yes | yes | coatings, silicone | emulgator | | | | DE, FR |
| 81325 | 25498-06-0 | polyvinyl cyclohexane | yes | | rubber | coagulating agent | | | | FR |
| _ | - | poly(vinyl methyl ether) | yes | | plastics | | | | | FR |
| 95755 | 25086-89-9 | Polyvinylpyrrolidone-vinyl acetate copolymer | yes | | plastics | PPA, pore- forming agent | | | The copolymer shall meet: - purity criteria for E 1208 as laid down in Reg (EU) No.231/2012, (suppl. Reg (EU) 1333/2008) - hydrazine content < 0.5 mg/kg; - oligomers below 1000 Da < 2%; - aldehydes content <500 mg/kg (as acetaldehyde) | DE |
| 81870 | 35674-65-8 | N,N"-1,3-propanediyl bis (N'-octadecylurea) | yes | | coatings | defoamer | | 0.0025 | | DE |
| _ | | propylene carbonate | yes | | lubricants | | | | | DE |
| 83530 | | quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides, compounds with bentonite | yes | | lubricants | | | | | DE |
| 83560 | 68953-58-2 | quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite | yes | | lubricants | thickener | | | | DE |
| - | 1503-48-6 | quino [2, 3-b]acridine-6,7,13,14(5H,12H)-tetrone (quinacridone quinone, QAQ), Purity > 90% QAQ | yes | | plastics | | 0.002 | | specific nanomaterial (> 50% 1-100 nm) in max. one particle dimension (platelets) | DE |

| | | | llee ee | llee ee | | | | | | |
|------------------|---------------------------------|---|-----------------------------|--|-------------------------|--------------------------------------|------------|------------------|---|----------|
| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
| | _ | reticulated cationic polyalkyleneamine a) epichlorhydric polyamide resin made from diaminopropylmethylamine and epichlorhydrin; b) epichlorhydric polyamide resin made from epichlorhydrin, adipic acid, caprolactam, diethylene triamine and/or ethylene diamine; c) epichlorhydric polyamide resin made from adipic acid,diethylene triamine and epichlorhydrin or a melt of epichlorhydrin and ammoniac; d) epichlorhydric polyamide-polyamide resin made from epichlorhydrin, dimethyladipate and diethylene triamine; e) epichlorhydric polyamide-polyamide resin made from epichlorhydrin, adipamide and diaminopropylmethylamine | yes | | plastics | | | | | FR |
| 85120 | 122-62-3 | sebacic acid, bis(2-ethylhexyl) ester | yes | | plastics | polymeric additive, platicizer | | | | FR |
| 85280 | 52829-07-9 | sebacic acid, bis(2,2,6,6-tetramethyl-4-piperidyl) ester | yes | | plastics, lubricants | lubricant | 0.3 | | | FR, NL |
| - | - | sebacic acid, reaction product with stearylamide, neutralised with calciumhydroxide | yes | yes | lubricants | thickener | | | | DE |
| 24445 | - | silanols, with at least one hydroxyl group and one or more methyl, vinyl or phenyl groups on every silicon atom | | yes | rubber | monomer | 0.0001 | | | NL |
| - | 68611-44-9 | silicium dioxide, reaction product with dimethyldichlorosilane | | yes | lubricants | thickener | | | DE: [1] | DE |
| 69885 | 68988-56-7 | silicium dioxide, reaction product with trimethylchlorosilane and isopropyl alcohol | | yes | lubricants | thickener | | | DE: [1] | DE |
| - | | silicone | yes | | rubber | polymeric additive | | | DE: [1] | DE |
| _ | 9006-65-9 | silicone oils (organopolysiloxanes with methyl and/or phenyl groups) | yes | yes | | polymeric additive, basic oil | | | DE: [1] | DE, FR |
| 86440 | ı | sodium aluminate | yes | | coatings | | | | | FR |
| 61340 | 149-44-0 | sodium hydroxymethanesulfinate | yes | | plastics | | | | max use level of 0.07% | DE |
| 21520 | 1561-92-8 | sodium methallyl sulfonate | yes | | plastics | | 0.25 | | | NL |
| - | - (among other 1318-02-1) | | yes | | | catalyst, additive | | 0.02 | MTC(T) for aluminium; Requirements for fillers apply | DE, FR |
| _ | - | solvents (boiling point < 150'C) if elimated in final product | yes | | coatings | solvent | | | | FR |
| - | | solvents in factory made products | yes | | | | 0.0001 | | | DE |
| _ | - | sorbitol esters with linear fatty acids, saturated or not, with an even number of carbon C8-C20 | yes | yes | coatings | | 0.0001 | | | FR |
| - | I | stearic acid mono or di esters with ethanediol and/or ether bis(2-hydroxyethyl) and/or triethyleneglycol | yes | | plastics | stabilizer | | | | FR |

| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|------------------|------------|--|-----------------------------|--|----------------------------------|------------------------------|--------------------------|------------------|--|----------|
| _ | ı | stearoyl-palmitoyl-benzoyl-methane | | yes | plastics | | | | | FR |
| _ | 68442-68-2 | styrene, reaction product with diphenylamine | yes | | rubber | stabilizer | 0.0025 | | | NL |
| _ | 126-33-0 | sulfolane | yes | | plastics | solvent | 0.0025 | | | NL |
| _ | 7446-09-5 | sulfur dioxide | yes | | rubber | monomer | | | | FR |
| _ | 10591-85-2 | tetrabenzylthiuram disulfide | yes | | rubber | accelerator | | | | FR |
| _ | 5593-70-4 | tetra-n-butyl titanate | yes | | plastics, rubber, silicone | accelerator | | | DE: [1] not for rubber | DE, FR |
| 92400 | 97-77-8 | tetraethylthiuram disulfide | yes | | plastics, rubber | expanding agent, accelerator | | NL: 0.05 | MTC(T) for the sum of tetra(alkyl/aryl)thiuram disulfides and tetramethylthiuram monosulfide | FR, NL |
| - | 811-97-2 | 1,1,1,2 -tetrafluoroethane | yes | | plastics | expanding agent | | | max. use level 2.2 % | FR |
| - | 3064-73-1 | tetra(isobutyl)thiuramdisulfide | yes | | rubber | | | 0.05 | MTC(T) for the sum of tetra(alkyl/aryl)thiuram disulfides and tetramethylthiuram monosulfide | NL |
| 92480 | 38613-77-3 | tetrakis(2,4-di-tert-butylphenyl)-2,4'-biphenylene diphosphonite | yes | | plastics, rubber | antifoaming | 0.9 | | | NL |
| - | 22288-41-1 | 1,1,3,3-tetramethylbutyl peroxypivalate | yes | | plastics | PPA, aids to polymerization | 0.001 | | max. 0.007% | DE |
| - | 681-84-5 | tetramethylorthosilicate | | yes | silicone | monomer | 0.085 (as Si) | | only for use in gas phase coatings on silicones | DE |
| 92720 | 137-26-8 | tetramethylthiuram disulfide | yes | | rubber | accelerator | | NL: 0.05 | MTC(T) for the sum of tetra(alkyl/aryl)thiuram disulfides and tetramethylthiuram monosulfide | FR, NL |
| _ | 97-74-5 | tetramethylthiuram monosulfide | yes | | rubber | accelerator | | NL: 0.05 | MTC(T) for the sum of tetra(alkyl/aryl)thiuram disulfides and tetramethylthiuram monosulfide | FR, NL |
| _ | 1 | titanic acid, esters with isobutanol, n-butanol and the enolate of ethylacetoacetate | yes | | silicone | catalyst | | | DE: [1] | DE |
| 25208 | 26471-62-5 | toluene diisocyanate | | yes | coatings | monomer | 0.06 | ND (<0.0001) | QM = 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety | DE, FR |
| _ | 104-15-4 | p-toluenesulfonic acid | yes | | plastics, rubber | accelerator | 0.0005 | | | FR, NL |
| _ | 93-69-6 | o-tolylbiguanidine | yes | | rubber | accelerator | FR: 0.0001 NL: 0.0025 | | | FR, NL |
| 25405 | 1025-15-6 | triallyl isocyanurate | yes | | rubber | activator | NL: 0.0001 | | | NL |
| 25445 | 28807-72-9 | tricyclododecane diisocyanate | | yes | coatings | hardener | | | QM = 1 mg/kg. QM and MTC(T) are both expressed as isocyanate moiety | DE |
| 25915 | 90-72-2 | 2,4,6-tri(dimethylaminomethyl)phenol | yes | | rubber, coatings | activator | 0.0001 | | | NL |
| - | 121-44-8 | triethylamine | yes | | plastics | | NL: 0.0001 | | DE: max 0.1% | DE, NL |
| _ | 78-40-0 | triethyl phosphate | yes | | plastics, coatings | | 0.375 | | | NL |
| - | 24748-23-0 | 3,6,9-triethyl-3,6,9-trimethyl-1,2,4,5,7,8-hexoxonane | yes | | plastics | PPA, aids to polymerization | 0.0001 | | DE: max. 0.05% | DE, NL |
| - | 13822-56-5 | 3-(trimethoxysilyl)propylamine | | yes | silicone | monomer | 0.085 (as Si) | | only for use in gas phase coatings on silicones, at max 400°C; Si/N ratio in the layer should be at least 11 | DE : |

| PM/ REF No | CAS No | Name | Use as additive, PPA, or AP | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS | | | |
|------------------|------------|---|-----------------------------|--|-----------|------------------------|------------|------------------|--|----------|--|--|--|
| _ | _ | trivinyl cyclohexane and α,ω- | yes | yes | silicon | monomer, | | | DE: max. use level 10 % [1] | DE | | | |
| | | dihydrogenpolyhydrogenmethyldimethyl-siloxanes, | | | rubber | polymeric | | | | | | | |
| | | addition products of | | | | additive | | | | | | | |
| _ | _ | urea-formaldehyde condensation products | yes | | plastics, | macromole-cular | | | intermediate according coating guideline | DE, NL | | | |
| | | | | | coatings | agent, polymer, | | | | | | | |
| | | | | | | resin, adhesive, | | | | | | | |
| | | | | | | hygroscopic | | | | | | | |
| | | | | | | agent | | | | | | | |
| _ | 7718-98-1 | vanadium chloride | yes | | plastics, | catalyst | | 0.0025 | MTC(T) expressed as vanadium | NL | | | |
| | | | | | rubber | | | | | | | | |
| _ | 11099-11-9 | vanadium oxide | yes | | plastics, | catalyst | | 0.0025 | MTC(T) expressed as vanadium | DE, NL | | | |
| | | | | | rubber | | | | DE: not for rubber | | | | |
| _ | _ | vinyl esters of monohydric, saturated, aliphatic carboxylic acids, C2-C20 | | yes | plastics | monomer | 0.0025 | | | NL | | | |
| 26230 | 88-12-0 | vinylpyrrolidone | yes | | plastics | lubricant | | | | DE, NL | | | |
| _ | 14726-36-4 | zinc dibenzyldithiocarbamate | yes | | rubber | accelerator | | NL: 0.05 | MTC(T) for the sum of all listed zinc- (alkyl/aryl)dithiocarbamates | FR, NL | | | |
| 96160 | 136-23-2 | zinc dibutyldithiocarbamate | yes | | rubber | accelerator | | NL: 0.05 | MTC(T) for the sum of all listed zinc- (alkyl/aryl)dithiocarbamates | FR, NL | | | |
| 96170 | 14324-55-1 | zinc diethyldithiocarbamate | yes | | rubber | accelerator | | NL: 0.05 | MTC(T) for the sum of all listed zinc-(alkyl/aryl) dithiocarbamates | FR, NL | | | |
| - | 137-30-4 | zinc dimethyldithiocarbamate | yes | | rubber, | accelerator, | | 0.05 | MTC(T) for the sum of all listed zinc-(alkyl/aryl) | NL | | | |
| | 100 50 0 | Line di O albudh avan anta | | | coatings | preservative | | | dithiocarbamates | DE NII | | | |
| - | 136-53-8 | zinc-di-2-ethylhexanoate | yes | | silicone | hardener | NII - O 4 | | QM = 1.5 % DE: [1] | DE, NL | | | |
| 96400 | 53801-45-9 | zirconium oxide | yes | | plastics, | stabilizer, | NL: 0.1 | | MTC is expressed as zirconium | FR, NL | | | |
| | | | | | rubber | antioxidant, | | | | | | | |
| | | | | | | drying agent | | | | | | | |

Annex C - Obsolete List (list of obsolete substances)

| PM/REF No | CAS No | Name | Use as additive, PPA or PA | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|--------------|------------|---|-------------------------------------|--|----------------------------------|------------------------|---------------|------------------|---|----------|
| _ | 3179-56-4 | acetyl cyclohexylsulfonyl peroxide | yes | | plastics | initiator | 0.0001 | | no peroxid on the product surface | DE, NL |
| _ | 25551-14-8 | 1,1'-azobis(1-cyclohexanecarbonitrile) | yes | | plastics | initiator | | | max. 0.2 % | DE, NL |
| _ | 2167-23-9 | 2,2-bis(tert-butylperoxy)butane | yes | | plastics | aids to polymerization | | | | DE |
| 38625 | 2781-00-2 | 1,4-bis(tert-butylperoxyisopropyl)benzene | yes | | plastics | visc. contr. agent | 0.0001 | | | NL |
| 40630 | 2782-40-3 | N-butylbenzamide | yes | | | | | | | FR |
| - | | calcium bis(2-ethylhexanoate) (= calcium octoate) | yes | | plastics | | | | | FR |
| 14587 | 1204-28-0 | 4-(chloroformyl)phthalic anhydride | | yes | coatings | monomer | 0.0025 | | QMA =0.05 mg/dm ² ; only for PTFE sintered | FR |
| _ | 2568-90-3 | dibutoxymethane (butylal) | yes | | plastics | | | | | NL |
| _ | | 2,6-di-tert-butyl-4-(methoxymethyl)phenol | yes | | rubber | protecting agent | 0.0001 | | | NL |
| _ | | dibutyltin diacetate | yes | | coatings, silicone | catalyst | | | | FR |
| _ | 4253-22-9 | dibutyltin sulfide | yes | | | | 0.002 | | expressed as tin | NL |
| - | 1717-00-6 | 1,1-dichloro-1-fluoroethane | yes | | plastics, coatings | expanding agent | | | | FR |
| _ | 68479-98-1 | diethylmethylbenzenediamine | yes | | | | | | | FR |
| - | 109-31-9 | dihexyl azelate | yes | | | | | | | FR |
| 48560 | | dihydro-1,4-dimethyl-2,6-dicarbododecyloxy-3,5-pyridine | yes | | plastics | stabilizer | | | | FR |
| 49040 | 1115-01-1 | 9,10-dihydroxystearic acid, methyl ester | yes | | plastics | lubricant | | | | FR |
| 49120 | 3271-22-5 | 2,4-dimethoxy-6-(1-pyrenyl)-1,3,5-triazine | yes | | plastics | azurant | | | | NL |
| _ | 793-24-8 | N-(1,3-dimethylbutyl)-N'-phenyl-p- phenylenediamine | yes | | rubber | | | | QM = 1.5% | FR |
| - | | dimethyldialkyl(C16 and/or C18)ammoniumacetate | yes | | plastics | | | | | NL |
| 75840 | 117-84-0 | di-n-octyl phthalate | yes | | plastics, rubber, coatings | plasticizer | 0.11 | | | NL |
| _ | 2432-87-3 | di-n-octyl sebacate | yes | | plastics, rubber | plasticizer | 0.0001 | | | NL |
| _ | 1 | N,N'-dioleoyl diaminoethane | yes | | | | | | | FR |
| _ | 5518-18-3 | N,N'-dipalmitoyl diaminoethane | yes | | coatings | | | | | FR |
| _ | | N,N'-distearoyl diaminoethane | yes | | coatings | | | | | FR |
| _ | 151-41-7 | dodecylsulfate | yes | | coatings, silicone | | | | | FR |
| 53040 | | 2-ethoxy-5-tert-butyl-2'-ethyloxalic acid bisanilide | yes | | plastics | | | | | FR |
| - | 75-04-7 | ethylamine | yes | | plastics | catalyst | | | | DE, NL |

| PM/REF No | CAS No | Name | Use as additive, PPA or PA | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|--------------|------------|--|-------------------------------------|--|-----------------------|-------------------------|---------------|------------------|--|----------|
| _ | | hexamethylenediamine carbamate | yes | | rubber | accelerator | | | | FR |
| - | 1191-25-9 | 6-hydroxyhexanoic acid | yes | | | | | 0.0025 | MTC(T) in this specific case means that the restriction shall not be exceeded by the sum of the migration levels of 6-hydroxyhexanoic acid and caprolacton (FCM No 342) | NL |
| _ | 59118-78-4 | 2-mercaptoethyl oleate | yes | | plastics | stabilizer, antioxidant | 1.5 | | | NL |
| _ | 96-45-7 | 2-mercaptoimidazoline | yes | | rubber | accelerator | 0.0025 | | | NL |
| _ | 96-53-7 | 2-mercaptothiazoline | yes | | rubber | accelerator | 0.0001 | | | FR, NL |
| 66000 | - | 3'-methoxy-4'-hydroxyphenyl-2-indole | yes | | plastics | stabilizer | | | | FR |
| _ | | N-methyldioctadecylamine | yes | | | | | | | NL |
| _ | 694-91-7 | 5-methylenebicyclo[2.2.1]hept-2-ene | yes | yes | rubber, coatings | monomer | 0.0025 | | | NL |
| 22333 | 79-11-8 | monochloroacetic acid | | yes | coatings | | 0.0025 | | | FR |
| _ | _ | monoethanolamine laurylsulfate | yes | | coatings | | | | | FR |
| - | 102-77-2 | morpholinothio-2-benzothiazole | yes | | rubber | accelerator | | 0.15 | MTC(T) in this specific case means that the restriction shall not be exceeded by the sum of the migrations levels of dithiobis(2-benzothiazole), 2,2' dibenzothiazyl disulfide, mercaptobenzothiazole, and 2-(4-morpholino)thiobenzothiazole | |
| _ | _ | myristyl polyethylene glycol (3-8) ether with oxyacetic acid | | yes | plastics | antistatic | | | | NL |
| 67900 | | naphtha | yes | | plastics | | | | | FR |
| 69120 | | oleic acid, butyl ester | yes | | plastics | | | | | NL |
| _ | 1912-84-1 | oleic acid, tin(II) salt | yes | | plastics | | 0.0025 | | | NL |
| _ | _ | 2-heptadecyl-4,4-bis (methylenestearate) oxazoline | yes | | coatings | | | | | FR |
| 70080 | 80-51-3 | 4,4'-oxybis(benzene sulfonyl hydrazide) | yes | | plastics | blowing agent | | | | FR |
| 70320 | 629-54-9 | palmitamide | yes | | coatings, silicone | catalyst | | | | FR |
| 71710 | | pentamethylenedithiocarbamic acid, piperidine salt | yes | | rubber | accelerator | | | | FR |
| _ | 13878-54-1 | pentamethylenedithiocarbamic acid, zinc salt | yes | | rubber | accelerator | | | | FR |
| _ | 79-21-0 | peracetic acid | yes | | | initiator | | | | FR |
| _ | 107-71-1 | peroxyacetic acid, tert-butyl ester | yes | | plastics | initiator | 0.0001 | | | DE, NL |
| _ | 1561-49-5 | peroxydicarbonic acid, dicyclohexyl ester | yes | | plastics | initiator | 0.0001 | | | DE, NL |
| _ | 105-64-6 | peroxydicarbonic acid, diisopropyl ester | yes | | plastics | initiator | 0.0001 | | | DE, NL |

| PM/REF No | CAS No | Name | Use as additive, PPA or PA | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|--------------|--------------------------|---|----------------------------|--|---------------------|---------------------------|---------------|------------------|--------------------------------|----------|
| 72105 | _ | phenols and/or cresols-styrene and/or alpha- methylstyrene and/or C3-C12 olefins, copolymers | yes | | rubber | | 0.0001 | | | NL |
| _ | _ | N-phenyl-N'-isohexyl-p-phenylenediamine | yes | yes | rubber | protecting agent | 0.0001 | | | NL |
| 72400 | 132-27-4 | 2-phenylphenol, sodium salt | yes | yee | rubber | preservative | 0.0001 | | QM = 0.02% | FR |
| 72560 | | 3-(2-phenyl)phenoxy-1,2-epoxypropane | yes | | plastics | procervative | | | QW 010270 | FR |
| 74000 | 78-42-2 | phosphoric acid, tris(2-ethylhexyl) ester | yes | | plastics | filler / pigments batches | | | | DE, FR |
| 74800 | _ | phthalic acid, di-heptyl/nonyl ester | yes | | rubber | plasticizer | | | | FR |
| 75040 | - | phthalic acid, diesters of hexadecanol and/or octadecanol | yes | | | | | | | FR |
| 75200 | 3648-61-1 | phthalic acid, diheptylic ester | yes | | plastics | plasticizer | | | | FR |
| - | 68410-23-1 83487-96-1 | polyaminoamide | yes | | rubber, coatings | macromolecular agent | 0.0001 | | | NL |
| - | _ | polyethylene oxide desorbitan monolaurate | yes | | coatings | emulgator | | | | NL |
| 23710 | 63148-65-2 | polyvinyl butyral | yes | | plastics | | | | | FR |
| _ | 11137-59-0 | potassium aluminate | yes | | rubber | buffering agent | | | | FR |
| _ | 74-98-6 | propane | yes | | plastics | pol.contr. agent | | | | NL |
| _ | _ | reaction products of styrene and/or methylstyrene and/or alkenes (C3-C12) with phenol and/or methylphenol | yes | | coatings | anchorage agent | 0.0025 | | | NL |
| 83650 | 9008-34-8 | resin acids and rosin acids, manganese salts | yes | | coatings | | 0.03 | | | FR |
| 83760 | _ | ricinoleic acid, amyl ester | yes | | plastics | | | | | FR |
| 83760 | _ | ricinoleic acid, butyl ester | yes | | plastics | | | | | FR |
| 83760 | _ | ricinoleic acid, ethyl ester | yes | | plastics | | | | | FR |
| _ | _ | rosin, dimerised, esters | yes | | plastics | | | | | FR |
| - | _ | rosin, hydrogenated, esters | yes | | plastics, rubber | | | | | FR |
| 86080 | | silicic acid, zirconium salt | yes | | plastics | lubricant, fillers | | | | DE, FR |
| _ | 10026-04-7 | silicon tetrachloride | yes | | plastics | catalyst | | | | DE, NL |
| _ | _ | soybean oil, modified with sulfur | yes | | plastics | lubricant | | | | NL |
| 89520 | | stearic acid, esters with pentaerythritol | yes | | plastics | | | | | FR |
| 89600 | | stearic acid, ethyl ester | yes | | plastics | | | | | FR |
| 90000 | | stearic acid, isobutyl ester | yes | | plastics | | | | | FR |
| 90480 | | stearic acid, pentyl ester | yes | | coatings | | | | | FR |
| 24560 | | stearic acid, vinyl ester | | yes | plastics | monomer | 0.0001 | | | DE |
| _ | _ | styrene (2 mol) condensed with 1 mol of a mixture of phenol and o-, m- en p-cresols, Brookfield viscosity of the end product at 25°c between 1400 and 1700 cP | yes | | plastics | polymeric additive | 0.0001 | | | NL |

| PM/REF No | CAS No | Name | Use as additive, PPA or PA | Use as monomer or other starting substance | Material | Technological function | MTC (mg/l) | MTC(T) [mg/l] | Restrictions and specification | Auth. MS |
|--------------|------------|----------------------------------|----------------------------|--|-----------------------|------------------------|---------------|------------------|--|----------|
| - | 1634-02-2 | tetrabutylthiuram disulfide | yes | | rubber | accelerator | | | MTC(T) in this specific case means that the restriction shall not be exceeded by the sum of the migrations levels of tetrabutylthiuram disulfide, tetraethylthiuram disulfide, tetramethylthiuram disulfide and tetramethylthiuram monosulfide | NL |
| 92960 | 111-17-1 | thiodipropionic acid | yes | | plastics, coatings | antioxidant | | | | FR, NL |
| _ | 11130-18-0 | titanium chloride | yes | | plastics | catalyst | | | | NL |
| _ | 7550-45-0 | titanium tetrachloride | yes | | plastics | other add. | | | | NL |
| 93790 | 102-82-9 | tributylamine | yes | | plastics | residue of catalyst | 0.0001 | | | DE, NL |
| _ | 106-10-5 | triethyleneglycol dioctanoate | yes | | | | | | | FR |
| _ | 10380-08-2 | triphosphoric acid | yes | | | | 0.0005 | | | FR, NL |
| 72060 | 89-03-8 | vasaline, pharmaceutical quality | | yes | rubber | plasticizer | | | | NL |
| 26290 | 25013-15-4 | vinyltoluene | | yes | plastics | monomer/ additive | | | | DE |
| 26215 | 100-69-6 | 2-vinylpyridine | | yes | rubber | monomer | | | | FR |
| - | 14634-93-6 | zinc ethylphenyldithiocarbamate | yes | | rubber | accelerator | | | MTC(T) in this specific case means that the restriction shall not be exceeded by the sum of all listed zinc-(alkyl/aryl) dithiocarbamates | NL |